

MK45S HYDRAULIC UNIT

THE MOST ADVANCED INDUSTRIAL TIGHTENING TOOL



INTERACTIVE SCREEN

The automatic MK45s Powerpack was designed to operate at factory with a high number of hydraulic tensioner. Different operational parameters can be set by the operator (pressure ramp, applied pressure time, etc) In addition, the Powerpack allows to maintain the pressure automatically between pre-programmed thresholds. The MK45s includes a handgrip that allows remote control.

Current Supply			LP oil flow	HP oil flow (1350)	Weigh	Máx. Pressure	Height	Width	Length
<i>Voltage</i>	<i>Frecuency</i>	<i>Current</i>	<i>l/m</i>	<i>l/m</i>	<i>kg</i>	<i>bar</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>
400 V	50 Hz	7 A	10,7	1	196	1500	1300	790	1000
400 V	60 Hz	7 A	10,7	1	196	1500	1300	790	1000

»» KEY ATTRIBUTE

- High Flow Unit. Build-up pressure flow: 10,7 l/min @187 bar/ 1 l/min @1350 bar
- PLC Controlled
- Manual mode & Automatic mode.
- With handgrip to remote control. Automatic release pressure using handgrip.
- Ramp mode programmable: The user can program different ramps during process.
- Automatic system to maintain or cut-off the pressure.
- Maintenance menu
- Safety system with enabling switches